

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD TITLE 29 CFR PART 1910.1200

Date of preparation: March 01, 2013 This MSDS supersedes all previous copies

Page 1 of 4

SECTION 1 CONTACT INFORMATION

CONCRETE EARTH LLC: 13087 MAIN STREET LEMONT, ILLINOIS 60439

24 HOUR EMERGENCY TELEPHONE	(800) 535-5053	INFOTRAC
MANUFACTURER CONTACT:	(800) 441-6646	CONCRETE EARTH LLC

TRADE NAME:	ECOGUARD PORE FILLER & DENSIFIER CONCENTRATE	NPCA HMIS RATINGS:
		Health: 1
PRODUCT CLASS:	Concrete polishing hardener & filler	Flammability: 1
		Reactivity: 0
PRODUCT APPEARANCE & ODOR:	Clear to slightly opalescent liquid, no noticeable odor	Personal Protection: B - gloves and goggles

SECTION 2: COMPOSITION - INFORMATION ON INGREDIENTS:

COMPONENT:	C.A.S.#	Percent by Weight	OSHA PEL TWA	ACGIH TLV TWA	NIOSH REL-TWA	NIOSH REL STEL
Proprietary resin Modified lithium-potassium silica	NA	36.00%	N.A.	N.A.	N.A.	N.A.
Water	7732-18-5	64.00%	None	None	None	N.A.

SECTION 3: PHYSICAL DATA

The following data represents approximate or typical values. They do not constitute product specifications

VAPOR PRESSURE	0.88 mm Hg (@ 20 deg C)	BOILING POINT:	>212°F (100°C) at 760 mm Hg
EVAPORATION RATE:	1.00 (Water = 1)	% VOLATILE	Approximately 64.00% +/- 2.50%
WEIGHT PER GALLON:	11.41 (lb/gal) +/-0.20	pH (10% in water):	Approx. 11.3 (+/-0.20)
SOLUBILITY IN WATER:	Dissoluble	V.O.C.:	<25 g/L .20 lb/gal
VISCOSITY	100 cps +/- 20 (Brookfield)	FREEZING POINT:	32°F (-0C)

SECTION 4: FIRE AND EXPLOSION DATA

FLAMMABILITY CLASS:	Not flammable (aqueous solution)
FLASH POINT:	>300 deg F
AUTOIGNITION TEMPERATURE:	N.A.
LOWER EXPLOSIVE LIMIT:	N.A.
SENSITIVITY TO STATIC DISCHARGE:	N.A.
EXTINGUISHING MEDIA:	Carbon dioxide, foam, dry chemical, water spray.
UNUSUAL FIRE AND EXPLOSION HAZARD	None
SPECIAL FIRE FIGHTING PROCEDURES:	Use air supplied rescue equipment for closed areas. Cool exposed containers with water.

SECTION 5: HEALTH HAZARD DATA

EFFECTS OF EXPOSURE:	
EYE CONTACT :	Minimal if any vapor concerns (due to low vapor pressure), however, product is irritating to the eyes if contact occurs inadvertently by splashing.
SKIN CONTACT:	Prolonged or repeated contact may cause irritation or reddening of the skin. <u>Non corrosive</u> to the skin.
INHALATION:	Not a likely route of exposure due to physical properties. Product has a very low vapor pressure at room temperature and is not expected to present an inhalation hazard under ambient conditions
INGESTION:	This product may be harmful if ingested.
CARCINOGENICITY:	Non hazardous by WHMIS/OSHA criteria. Not listed by IARC, NTP, or ACGIH.

SECTION 6: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:	Flush eyes with large amounts of water until irritation subsides. Seek medical attention if necessary.
SKIN CONTACT:	Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists. Remove contaminated clothing and laundry before re-use.
INHALATION:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and seek medical attention.
INGESTION:	If swallowed, <u>do not</u> induce vomiting. If conscious, give 3-4 glasses of water to dilute and get immediate medical care. Never give anything by mouth to an unconscious person.

SECTION 7 REACTIVITY DATA

STABILITY:	Product is considered stable at regular temperatures.
CONDITIONS TO AVOID:	None known.
INCOMPATIBILITY (MATERIALS TO AVOID):	Avoid contact with strong oxidizers, acids, and alkalis.
HAZARDOUS DECOMPOSITION PRODUCTS:	Thermal decomposition may yield , but not limited to oxides of carbon.
HAZARDOUS POLYMERIZATION:	Will not occur.

SECTION 8: ACCIDENTAL RELEASE & DISPOSAL MEASURES

LEAK AND SPILL PROCEDURE:	Collect for disposal. Clean up remaining materials from spill with suitable absorbent. Small spills may be absorbed with non-reactive absorbent (sand) and placed in a suitable, covered, labeled container. Prevent spills from entering sewers or waterways. Observe all personal protection equipment recommendations.
WASTE DISPOSAL:	Dispose of in accordance with local, state and federal regulations.

TRADENAME: ECOGUARD PORE FILLER & DENSIFIER CONCENTRATE

Page 3 of 4

SECTION 9: SAFE HANDLING AND USE INFORMATION:

RESPIRATORY PROTECTION:	Not normally required with this product.
VENTILATION/ ENGINEERING CONTROLS:	Not normally required
PROTECTIVE GLOVES:	Use impervious (rubber or nitrile) gloves
EYE PROTECTION:	Use chemical safety/splash goggles
OTHER PROTECTIVE EQUIPMENT:	Impervious clothing or boots, if needed.
HANDLING PROCEDURES:	The usual precaution for the handling of chemicals must be observed.
DEPT. OF LABOR STORAGE CATEGORY:	Not regulated
STORAGE CONDITONS:	Store under cool, dry conditions and away from temperature extremes. The minimum recommended storage temperature for this material is 1 C/34F. The maximum recommended storage temperature is 49C/120F. Keep from freezing. If frozen, product needs to be tested before using for emulsion stability.
WORKPLACE CLASSIFICATION:	This product as supplied is non-hazardous under the OSHA Hazard Communication Standard (20 CFR 1910.1200).

SECTION 10: TOXIOLOGICAL INFORMATION

CARCINOGENITY:	Non hazardous by WHMIS/OSHA criteria. Not listed by IARC, NTP, or ACGIH.
ACUTE SKIN IRRITATION/CORROSION TEST:	N.A.

SECTION 11: ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE:	N.A.
FISH, ACUTE TOXICITY TEST, OECD 203	N.A.

SECTION 12: TRANSPORT AND SHIPPING INFORMATION

U.S. DEPT. OF TRANSPORTATION -ROAD OR RAIL:	Not regulated
U.S. DEPT. OF TRANSPORTATION - PROPER SHIPPING NAME:	Concrete polishing pore and crack filling concentrate
CANADIAN T.D.G.:	Not regulated
IMO WATER TRANSPORTATION:	Not regulated
IATA AIR TRANSPORTATION:	Not regulated

SECTION 13: REGULATORY INFORMATION

OCCUPATIONAL HEALTH & SAFETY REGULATIONS:	
WHMIS CLASSIFICATION	N.A.

TRADENAME: ECOGUARD PORE FILLER & DENSIFIER CONCENTRATE

Page 4 of 4

SECTION 13: REGULATORY INFORMATION (CONTINUED)

ENVIRONMENTAL REGULATORY LISTS:	
SARA SECTION 313:	(Toxic Chemical Release Reporting) 40 CFR 372- None of the ingredients are listed.
TSCA (TOXIC SUBSTANCES CONTROL ACT):	All the ingredients are listed on the Chemical Substance Inventory
CANADIAN DSL:	All ingredients are listed.
CALIFORNIA PROPOSITION 65:	The following components of this product are substances, or belong to classes of substances, known to the state of California to cause cancer and/or reproductive toxicity: Chemical Name: None

USERS RESPONSIBILITY AND DISCLAIMER OF LIABILITY: Concrete Earth LLC, assumes no liability in connection with any use of this information. As the handling and use of products under user's conditions are beyond our control, no warranty, expressed or implied, including, but not limited to merchantability or fitness for a particular use, is made concerning this product. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. The user assumes all risk of use or handling whether or not in accordance with any directions or suggestions of the supplier. Seller shall not be liable to purchaser or any other person for loss or damages directly or indirectly arising from the use of our products, from breach of warranty or from any other cause, the exclusive remedy against the seller being to require replacement or repair of defective goods. All statements, information, recommendations and data provided in this material data safety sheet are believed to be accurate and reliable, but are presented without any guarantee. Users should make their own investigations to determine the suitability of the information or products for their particular purposes. Refer to 49 CFR (Code of Federal Regulations) for possible exceptions and exemptions.

Abbreviations: CFR=Code of Federal Regulations, OSHA = Occupational Safety and Health Administration. NIOSH = National Institute of Occupational Safety and Health. ACGIH = American Conference of Governmental Industrial Hygienists. TLV = Threshold Limit Value (8-hr. TWA). TWA= Time Weighted Average. STEL= Short Term Exposure Limit (15 min. TWA). N.A. = Not Applicable. PEL = Permissible Exposure Limit (8-hr. TWA).

Date of preparation: 04-01-13- Supersedes all previous copies