

ECOGUARD

THE GREEN ALTERNATIVE FOR POLISHED CONCRETE FLOORS

ECOGUARD™ Daily Cleanser

Concrete Earth's ECOGUARD™ Daily Cleanser offers all of the advantages of high grade commercial cleaners and degreasers in a pH neutral base and a 100% Green solution. ECOGUARD™ Daily Cleanser is organically enhanced and provides an excellent daily maintenance program for long term sanitation solutions.

ECOGUARD™ polished concrete floors are easier to maintain, retain a maximum gloss with periodical high speed burnishing. ECOGUARD™ Daily Cleanser uses high quality organic compounds and is an ideal cleaner for all types of hard flooring surfaces. Ideal uses are for concrete, terrazzo, and stone tile floors, commercial concrete flatwork or decorative stamping exposed to high traffic such as terminals, lobbies, showroom floors, restaurants, schools, malls, as well as residential living spaces.

BENEFITS:

- A HIGH CONCENTRATE ORGANIC NEUTRAL FLOOR CLEANER
- EXCELLENT DEGREASER AND EMULSIFIER
- PROVIDES ADDED WATER REPELLENCE
- EASILY RINSED OFF WITH NO SOAP FILM RESIDUE
- EXTENDS THE USEFUL LIFE OF ECOGUARD™ MAXGLOSS PROTECTIVE BARRIER
- ENHANCES SURFACE GLOSS WITHOUT HIGH SPEED BUFFING
- 100% GREEN SOLUTION AND COMPLETELY ENVIRONMENTALLY FRIENDLY

COMPOSITION: ECOGUARD™ Daily Maintenance Cleaner is the combination of a neutral basic cleaner and specially modified organic compounds in aqueous solution with an added resin for water & stain repellence.

| PHYSICAL PROPERTIES | APPROXIMATE VALUES at 70° F (21°C): |
|---|-------------------------------------|
| Weight per Gallon: | 8.52 +/- 0.10 lb./ gallon |
| pH: | 7.0 +/- 0.2 |
| %Solids (Concentrate): | 80.0% +/- 1.0 |
| Color: | Light Blue |
| Freeze Point: | 30°F (-1.1°C) |
| VOC (Volatile Organic Compounds) diluted: | <100 g/L (0.50 lb./gal) |

APPLICATION INSTRUCTIONS:

TEST AREA: Always test ECOGUARD™ Daily Cleanser on a small area of the surface to be treated before overall application to determine suitability and results. Use a test location that is out of the way and not in the main area of the final area.

APPLICATION: Pour Concrete Earth ECOGUARD™ Daily Cleanser into your auto scrubber clean water tank, fitted with the ECOGUARD™ Daily Maintenance Cleaning Pad under the ECOGUARD™ Warranty. Dilute 1 oz of Daily Cleanser to 1 Gal. of water for daily cleaning maintenance. For heavy duty grease removal, use up 4-8 oz of Daily Cleanser per gallon of water. On direct oil spills, you may pre-soak with a 1:1 mix to break down and emulsify heavy grease/oil based surface contamination. To clean using a mop and mop bucket, saturate the mop in the recommended diluted solution, squeeze out excess material and disperse freely. Use a bucket wringer and mechanically compress out. Once complete, use a clean water rinse to remove all contaminants embedded in the Daily Cleanser diluted solution. The use of a high speed buffing machine is recommended to obtain optimal gloss and shine once dry.

COVERAGE: Approximately 1,500-2,000 square feet per gallon (36.8-49.0 square meters / liter).



ECOGUARD

WARNINGS: ECOGUARD™ Daily Cleanser is harmful if swallowed. It is also an eye irritant and may irritate skin. Wear protective safety glasses, gloves, and clothing when handling. Avoid prolonged skin contact-wash skin with soap and water if exposed to avoid irritation. Refer to product M.S.D.S. (Material Safety Data Sheet) for further health and safety information. Keep containers closed when not in use and dispose of accordingly. Keep away from food and drink. **DO NOT TAKE INTERNALLY. FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. FOR MEDICAL EMERGENCIES ONLY, CALL INFOTRAC 800-535-5053.**

H.M.I.S. CODES (Hazardous Materials Identification System):

HEALTH = 1, FLAMMABILITY = 0, REACTIVITY = 0, PERSONAL PROTECTION = C

SHIPPING CLASS: ITEM 33880, SUB 2, LTL 55 CONCRETE SEALER-WATER BASE-NOT REGULATED BY D.O.T.

PACKAGING: 1 gallon (4 / case) and 5 gallon containers

STORAGE: 40° to 90° F. Keep from freezing

SHELF LIFE: 2 year properly stored

WARRANTY: Concrete Earth, LLC (CE) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of CE, no other representations or statements made by CE or its representatives, in writing or orally, shall alter this warranty. **CE MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME.** If any CE product fails to conform with this warranty, CE will replace the product at no cost to Buyer. **Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages.** CE does not authorize anyone on its behalf to make any written or oral statements which in any way alter CE's installation information or instructions in its product literature or on its packaging labels. **CE explicitly excludes any written or oral statements or implied warranty on the performance of an applied/installed product manufactured or sold by or through CE. CE has no control over CE application standards adherence, site conditions, atmospheric variations, installer/applicator skill level or the determination of the suitability of any CE products for a specific intended purpose. Buyer shall be solely responsible for determining the suitability of CE's products for the Buyer's intended purposes.** Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind.

Revised: 8-15-14